

High Performance Sub-Master Clock Unit

Product Overview

Valiant's VCL-2103 SUB-MASTER CLOCK is a high-performance intermediate time synchronization source which may be directly synchronized to a Primary GPS Reference (Master) Clock or any other NTP time source to provide Time-of-Day synchronization to secondary NTP / SNTP Slave devices in the network. The VCL-2103 Sub-Master Clock mediates between the Primary GPS Reference (Master) Clock or any other time source and the Slave NTP / SNTP devices, such as Time-Of-Day Display Clocks in a LAN, to effectively isolate the GPS Primary Reference Clock Source from the NTP / SNTP Slave devices and provide NTP / SNTP time-of-day synchronization with millisecond accuracy.



The VCL-2103 Sub-Master Clock provides two distinctly separate Ethernet Ports, each of which is assigned its own IP address which allows the VCL-2103 Sub-Master Clock to synchronize with the Primary GPS Reference (Master) Clock and to also provide time synchronization to multiple Slave NTP / SNTP devices in a LAN network.

Multiple VCL-2103 Sub-Master Clock Units can be installed in a network to synchronize with the Primary GPS Reference (Master) Clocks to provide 1+1 or n+1 source redundancy in a NTP / SNTP time synchronization network.

Features, Highlights and Options:

- IPv4 compliant Sub-Master Clock
- Ethernet 10/100BaseT, NTP / SNTP Date and Time Synchronization
- EEPROM for setting retention after power down
- High-Performance NTP Server running at 533MHz clock speed
- Unmatched security. Password Protection and Firewall. Resistant to DOS (Denial of Service) attack and unauthorized access
- Capable of serving up to 1500, VCL-2106 Slave Display Clocks or other standard / third party NTP/SNTP Clients

Input:

- 1 x 10/100/1000BaseT Ethernet NTP Input Port with automatic synchronization to redundant NTP Server(s) based upon Stratum level of source for master clock synchronization.

Output

- 1 x 10/100BaseT Ethernet NTP / SNTP Output Ports for slave device(s) synchronization

Reliability and Timing Accuracy:

- May be provisioned in a 1+1, or n+1 redundant configuration.
- Dual OCXO based, extremely high (best in class) internal clock accuracy.
- The clock drift is less than ± 0.001 second in a 24 hour time-period / 0.5 second per year (in the temperature range of -10C to +50C) in the event of loss of synchronization of the referenced time source.

Environmental:

- Temperature:
 - Operating Range: -20C to +65C
 - Storage: -40C to +75C
- Humidity 0-95% (without condensation)
- Altitude: Up to 3000 meters
- Industrial Hardened Design. Non-corrosive chassis.
- Protection: IP 30

Certification:

- CE and FCC approval
- Conducted Immunity as per IEC 61000-4-6
- Radiated Immunity IEC 61000-4-3
- Meets and exceeds CISPR 22 / EN55022 Class B emission requirements
- Voltage and Surge Withstand: Meets and exceeds
- IEC 61000-4-2, IEC 61000-4-4, IEC 61000-4-5 specifications.
- Interruptions and Voltage variations meets and exceeds IEC 61000-4-11 specifications.

Local / Remote Management and Monitoring Ports:

- RS-232C
- USB
- 10/100BaseT Ethernet RJ45
- 1 x External Alarm Relay Contact

Local / Remote System Access, Control and Management Options:

- Telnet, SSH
- Online Firmware upgrade
- CLI Control Interface (HyperTerminal or VT100)
- SNMP V2 Traps (MIB File provided)

MTBF (Mean Time Between Failure):

- Per MIL-HDBK-217F: > 25 years @ 40C
- Per Telcordia SSR 332, Issue 1: > 29 years @ 40C

Power Supply Options*:

- 24V DC
- 48V DC
- 110V DC
- 90V AC-240V AC, 50/60 Hz
- 1+0 and 1+1 Dual Redundant Power Supply Options

Power Consumption:

- < 10 Watts

Description: VCL-SMC, Sub Master Clock:

- Remote Management over TCP-IP Network
- 19-Inch, 1U
- 1 x NTP, 10/100/1000BaseT Ethernet Input Ports (NTP Receiver / Client Port)
- 1 x NTP / SNTP, 10/100BaseT Ethernet Output Ports (NTP Host / Server Port)

Ordering Information and Dimensions:

Version	Width	Height	Depth	Weight
VCL-2103	480 mm	44 mm	250 mm	2.2 kgs

* Please specify the required power supply option.

Technical specifications are subject to changes without notice.
All brand name and trademarks are the property of their respective owners.
Revision 2.3A - February 27, 2017

U.K.

Valiant Communications (UK) Ltd
1, Acton Hill Mews,
310-328 Uxbridge Road,
London W3 9QN
United Kingdom
E-mail: gb@valiantcom.com

U.S.A.

Valcomm Technologies Inc.
4000 Ponce de Leon, Suite 470
Coral Gables, FL 33146
U.S.A.
E-mail: us@valiantcom.com

INDIA

Valiant Communications Limited
71/1, Shivaji Marg,
New Delhi - 110015,
India
E-mail: mail@valiantcom.com